



- NL** Lichtlopende draagrol met aan de binnenzijde gesloten kunststof lagerpotten, voorzien van een roestvaststalen conuslager. Geschikt om middelzware producten op een zwaartekrachtbaan te transporteren, daar waar geen water, bacteriën, etc. de rol mogen binnendringen. Speciaal voor toepassingen in de voedingsindustrie.
- D** Leichtlauf-Tragrolle mit an den Innenseiten geschlossenen Kunststoff-Lagerböden und Niro-Konuslagern. Geeignet um mittelschwere Produkte auf einer Schwerkraftbahn zu transportieren, dort wo ein Eindringen von Wasser, Bakterien etc. ins Rohrinne unterbunden werden soll. Einsatz insbesondere Nahrungsmittelindustrie
- GB** Free-running conveyor roller with inside plastic sealed bearing, fitted with a stainless steel conical bearing. Suitable for transporting medium-heavy products on a gravity conveyor in locations where no water, bacteria, etc. may penetrate the roller. Especially for applications in the food industry.

SPECIFICATIONS:



PPco

SS 1.4301
con. bearing

25 KG



WHITE

Tube	Steel Zinkplated	Stainless steel	PVC 5005	PVC 7011
Ø 50 x 1.5	x	x		
Ø 50 x 2.0	x	x		
Ø 50 x 2.8			x	x
Ø 60 x 1.5	x			
Ø 60 x 2.0	x	x		
Ø 63 x 3.0			x	x
Ø 63.5 x 2.9	x			
Ø 80 x 2.0	x	x		
Ø 82.5 x 3.2	x			
Ø 88.9 x 3.2	x	x		
Ø 90 x 7.0			x	x